

AquaCafé®

Single Serve Coffee & Tea Brewer

Model ACB520P: Pod Brewer

Model ACB520K: Capsule
Brewer / K-Cup® Compatible



Features

- 0.8L / 0.21G stainless steel hot tank
- 40,000 cycles vs. home systems at 4,000 - 8,000 cycles
- Single-serve coffee & tea in about 45 seconds
- Brews 6, 8, 10, 12, and 14 ounce cup sizes with a variety of pod flavors (sold separately)
- Counter top model either pour-over tank or plumbed
- Touch screen interface
- Sealed controls keep out dirt and liquid
- One touch dispensing of hot water in addition to the brew function
- Simple three-step brewing — (1) insert pod, (2) select a cup size, and (3) press brew
- Safety lock function for hot water
- Additional fold-down drip tray to accommodate a variety of container shapes and sizes
- Auto eject — no touching of used pods
- Integrated trash bin holds up to 30 used pods
- Energy Saver and sleep modes
- **Model ACB520P: Pod Brewer**
- **Model ACB520K: Capsule Brewer / K-Cup® Compatible**
- **CUL Listed**

Power

Voltage	120V
Frequency (Hz)	60
Total Power Consumption	12.5A / 1500W / 120V
Total Power Consumption (AH)	11.5A / 1305W / 115V

Hot Water System

Avg. Hot Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	172°F / 190.4°F
Brewing Temperature	194°F
Hot Water ARI Rating	45, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	221°F (Safety)
Hot Thermostat / Thermistor Cycle	215.6°F - 226.4°F
Hot Water Flow Rate	0.18 oz./sec
Hot Tank Size (Liter : Gallon)	0.8L : 0.21G
Hot Tank Material	304 Stainless Steel

Weights and Measurements

Net Weight (Lbs.)	21.16
Gross Weight (Lbs.)	23.8
Max Distance from Drip Tray to Faucet (Adjustable) (Inch : mm)	7.56 : 192.02
Boxed Dimensions WxDxH (inch : mm)	20.47x14.8x19.29 : 519.93x375.92x489.96
Model	ACB520P / ACB520K
Certifications	CUL Listed, Energy Star Rated
Warranty	2 Years Parts



Toll Free: 800-459-2882

Phone: 604-882-6940

Fax: 604-882-6870

EMAIL: info@newtechbeverage.com